



# De Plaatijzerindustrie BV

Kayersdijk 131, NL-7332 AP Apeldoorn  
 P.O. Box 46, NL-7300 AA Apeldoorn  
 sales.heads@plaatijzerindustrie.com

Tel. +31.(0)55.5333.717

Korbbogen heads (R=0,8D r=0,154D) - DIN 28013								
General information					Material			
Diam. (D) outside (mm)	Thickness (S) (mm)	Height (H) outside (mm)	Capacity (litre)	Weight (kg)	S235JRG2	P265GH	1.4301	1.4404
168	3	64	1,03	1,1				NS
168	5	65	0,9	1,8		ST		
168	10	83	0,85	4		ST		
273	5	93	3,45	4,2				ST
273	7	97	3,58	6,1		ST		
273	10	110	3,62	9,2		NS		
298	7	103	4,56	7,1	NS			
324	5	106	5,57	5,7	NS			ST
324	10	123	5,83	12,4	NS			
350	3	110	7,15	3,9	ST		NS	ST
350	5	112	6,92	6,6		ST		
356	8	129	7,97	11,9		ST		
356	12	142	8,22	18,7		ST		
406	5	127	10,46	8,7	ST			ST
406	6	130	10,4	10,8		ST		
406	10	144	10,94	18,8		ST		
419	5	130	11,52	9	ST			
450	5	137	14,21	10,6		ST		
457	12	168	16,44	29,5		ST		
500	5	150	19,06	13		ST		
508	8	167	20,23	22,9		ST		
508	11	180	22,34	32,7		ST		
550	3	161	25,58	9,4				ST
550	7	168	25,85	20,3		ST		
560	12	189	29,04	42,4		ST		
600	4	175	32,47	14,7				ST
600	5	176	32,17	18,4		ST		
609	10	195	34,73	39,4		ST		
700	5	201	50,18	24,8		ST		
700	8	216	50,78	41,6		ST		
712	11	232	57,66	61		ST		
750	3	212	62,23	17,1				ST
750	6	217	60,8	34,4		ST		
762	12	241	69,45	75		ST		
800	8	232	74,71	54		ST		
800	11	255	80,23	76		ST		
900	6	255	103,4	49		ST		
950	6	268	121	54		ST		
1000	6	280	141	61		ST		

\* Heads with a centerhole 36mm.

ST = standard

NS = non standard

nov-23