



De Plaatijzerindustrie BV

Kayersdijk 131, NL-7332 AP Apeldoorn
 P.O. Box 46, NL-7300 AA Apeldoorn
 sales.heads@plaatijzerindustrie.com

Tel. +31.(0)55.5333.717
 Fax +31.(0)55.5423.943

Low pressure heads (R=1,2D till 1,4D)								
General information					Material			
Diam. (D) outside (mm)	Thickness (S) (mm)	Height (H) outside (mm)	Capacity (litre)	Weight (kg)	S235JRG2	P265GH	1.4301	1.4404
250	3	51	1,7	2	ST			
300	3	65	2,6	2,6	ST			
350	3	65	3,8	3,2	ST			
380	3	85	4,6	4,5	ST			
400	2	70	5,3	3,1	ST			
400	3	75	5,3	4,7	ST			
450	3	83	7,1	5,7	ST			
500	3	110	9,3	7,2	ST			
500	5	110	9,1	12,4	ST			
550	5	115	11,6	13,9	ST			
600	3	115	14,8	10,3	ST			
600	5	128	14,6	17,2	ST			
650	3	123	10,8	11	ST			
650	5	123	18	17,2	ST			
700	4	105	24,9	14,5	ST			
750	3	135	30	15,6	ST			
750	5	120	29,6	21,6	ST			
800	3	110	35,4	14,1	ST			
800	5	105	35	24,8	ST			
900	4	128	47,8	23,6	ST			
1000	4	140	63,1	28,8	ST			
1100	5	180	80,9	53	ST			
1270	4	175	119,4	47,5	ST			

Remarks:

Capacity en weight are based on
 r=15mm en h=15mm (from 200mm till 650mm)
 r=20mm en h=20mm (from 700mm till 1270mm)

ST = standard
 NS = non standard